

Class 46: Variable-Arity Procedures

Held: Monday, 20 November 2006

Summary: Today we consider how and why to write procedures that can take different numbers of arguments in different situations.

Related Pages:

- EBoard.
- Lab: Variable-Arity Procedures.
- Reading: Variable-Arity Procedures.

Notes:

- Time for questions on HW 16.

Overview:

- Definition of *arity*.
- Why have variable-arity procedures.
- How to write variable-arity procedures.
- Lab.

Variable-Arity Procedures

- Def. *Arity*: The number of parameters a procedure expects.
- Some procedures naturally take varying numbers of parameters:
 - `+` takes 0 or more parameters.
 - `display` takes 1 or 2 parameters.
 - `map` takes 2 or more parameters.
- It would be nice to be able to write our own procedures of variable arity (that is, varying numbers of parameters).
- Zero or more parameters:

```
(lambda params  
  body)
```

- `params` is *not* parenthesized.
- In your body, treat `params` as a list.
- One or more parameters:

```
(lambda (first . remaining)
  body)
+ In your body, treating remaining as a list.
```

- Two or more parameters:

```
(lambda (first second . remaining)
  body)
+ In your body, treating remaining as a list.
```

Lab

- Do the laboratory entitled Variable-Arity Procedures.
 - Be prepared to reflect.
-

Copyright © 2006 Samuel A. Rebelsky. This work is licensed under a Creative Commons Attribution-NonCommercial 2.5 License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc/2.5/> or send a letter to Creative Commons, 543 Howard Street, 5th Floor, San Francisco, California, 94105, USA.